

# SAFETY DATA SHEET

PRODUCT CODE: 100HV

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** AG100HV-X part A  
**PRODUCT CODES:** 100HV A

**MANUFACTURER:** ArmorGarage  
**STREET ADDRESS:** 1260 North Ave  
**CITY, STATE, ZIP:** Plainfield NJ 07062

**INFORMATION PHONE:** 724-483-9300  
**EMERGENCY PHONE:** Chemtrec 800-424-9300  
**FAX PHONE:** 724-483-9306

**PREPARED BY:** Harry Jackson

**DATE REVISED:** 8/02/24

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
REACTION PRODUCTS OF EPICHLOROHYDRIN					
BISPHENOL A	25068-38-6	NONE	NONE	NONE	
MODIFIED DIGLYCIDYL ETHER OF					
BISPHENOL A	25068-38-6	NONE	NONE	NONE	
ALKYL GLYCIDYL ETHER	68609-97-2	NONE	NONE	NONE	
PIGMENT (non-hazardous in liquid form)	N/A	10mg/m3	10mg/m3	5mg/m3	
STODDARD SOLVENT	8052-41-3	100ppm	100ppm	NONE	
1-METHOXY-2-PROPANOL ACETATE	108-65-6	NONE	NONE	NONE	
PROPRIETARY ADDITIVE (less than 1%)	N/A	NONE	NONE	NONE	
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	100ppm	100ppm	NONE	
PROPRIETARY ADDITIVE (less than 1%)	N/A	NONE	NONE	NONE	
PROPRIETARY NON-HAZARDOUS ADDITIVES	N/A	NONE	NONE	NONE	
Carbon black	1333-86-4	3.5 ppm	3.5 ppm	none	

No toxic chemicals subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

## SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** LOW VISCOSITY LIQUID – VARYING COLORS  
**BOILING POINT OR RANGE:** 200 TO 315 ° F:  
**VAPOR DENSITY (AIR = 1):** N/A  
**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.2  
**EVAPORATION RATE:** N/A  
**SOLUBILITY IN WATER:** NEGLIGIBLE

SECTION 3 NOTES:

## SECTION 4: FIRE-FIGHTING MEASURES

**FLAMMABLE LIMITS IN AIR,** UPPER: N/A  
(% by volume) LOWER: N/A

**FLASH POINT:** 200 + F

**METHOD USED:**

SETA FLASH

**EXTINGUISHING MEDIA:**

FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL, WATER FOG

**SPECIAL FIRE FIGHTING PROCEDURES:**

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

NO UNUSUAL FIRE HAZARDS KNOWN.

SECTION 4 NOTES:

## SECTION 5: STABILITY AND REACTIVITY

**STABILITY:**

STABLE

**CONDITIONS TO AVOID (STABILITY):**

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

# MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 100HV

## INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

## HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO<sub>2</sub>, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

## HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

## SECTION 5 NOTES:

---

## SECTION 6: HAZARDS IDENTIFICATION

---

### HMIS HAZARD CLASSIFICATION

HEALTH: 2      FLAMMIBILITY: 1      REACTIVITY: 0      PERSONAL PROTECTIVE EQUIPMENT: G

### POTENTIAL HEALTH EFFECTS

#### EYES:

MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

#### SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE. NOT LIKELY TO BE ABSORBED IN TOXIC AMOUNTS.

#### INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

#### INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES.

#### HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

#### CARCINOGENICITY

OSHA: NO      NTP: NO      IARC: yes

#### ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B.

---

## SECTION 7: FIRST AID MEASURES

---

### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

### SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

### INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, OTHERWISE DO NOT INDUCE VOMITING AND CONSULT A PHYSICIAN.

### INHALATION:

REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY. CONSULT PHYSICIAN IF NECESSARY.

### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

## SECTION 7 NOTES:

---

## SECTION 8: RELEASE MEASURES

---

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBANT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

## SECTION 8 NOTES:

---

## SECTION 9: WASTE DISPOSAL

---

### WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

---

## SECTION 10: HANDLING AND STORAGE

---

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

# MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 100HV

STORE IN COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFOR, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

## OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

## SECTION 10 NOTES:

---

## SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

### VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

### PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

### EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERING AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

### WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

## SECTION 11 NOTES:

---

## SECTION 12: DISCLAIMER

---

**DISCLAIMER:** THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

**PRODUCT NAME:** AG100HV-X PART B  
**PRODUCT CODES:** 100HV B

**MANUFACTURER:** ArmorGarage  
**STREET ADDRESS:** 1260 North Ave

# MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 100HV

CITY, STATE, ZIP: Plainfield NJ 07062

INFORMATION PHONE: 724-483-9300  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 724-483-9306

PREPARED BY: Harry Jackson

DATE REVISED: 8/02/24

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	
3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE	2855-13-2	NONE	NONE		
2-HYDROXYBENZOIC ACID	69-72-7	NONE	NONE	NONE	
SYNTHETIC AMORPHOUS PRECIPITATED SILICA	7631-86-9	20mg/m3	NONE		

No toxic chemicals subject to the reporting requirements of section 313 of title III and of 40 CFR 372 are present.

## SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: AMBER CLEAR LIQUID WITH AMINE ODOR  
BOILING POINT OR RANGE: 401 TO 477 ° F  
VAPOR DENSITY (AIR = 1): N/A  
SPECIFIC GRAVITY (H2O = 1): 1.0  
EVAPORATION RATE: N/A  
SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 3 NOTES:

## SECTION 4: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, (% by volume) UPPER: N/A  
LOWER: N/A

FLASH POINT: 200 +F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTERS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN

SECTION 4 NOTES:

## SECTION 5: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO2, NOX

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

SECTION 5 NOTES:

## SECTION 6: HAZARDS IDENTIFICATION

# MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 100HV

## HMIS HAZARD CLASSIFICATION

HEALTH: 2      FLAMMIBILITY: 1      REACTIVITY: 0      PERSONAL PROTECTIVE EQUIPMENT: G

## POTENTIAL HEALTH EFFECTS

### EYES:

WILL CAUSE BURNS TO THE EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

### SKIN:

WILL CAUSE BURNS TO THE SKIN

### INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

### INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA AND DIZZINESS.

### HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS

### CARCINOGENICITY

OSHA: NO      NTP: NO      IARC: NO

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

### ADDITIONAL CARCINOGENICITY INFORMATION:

---

## SECTION 7: FIRST AID MEASURES

### EYES:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

### SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

### INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

### INHALATION:

REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

### SECTION 7 NOTES:

---

## SECTION 8: RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBANT AND PLACE IN DISPOSAL CONTAINERS.

### SECTION 8 NOTES:

---

## SECTION 9: WASTE DISPOSAL

### WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, & LOCAL REGULATIONS.

---

## SECTION 10: HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

### OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

---

## SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

### RESPIRATORY PROTECTION:

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

### VENTILATION:

# MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 100HV

AVOID BREATHING VAPORS, VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES, NEOPRENE OR RUBBER.

**EYE PROTECTION:**

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

CLEAN BODY COVERING CLOTHING AS WELL AS APRON FOOTWEAR OR OTHER EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH THE MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GENERAL GOOD HYGIENIC PRACTICES.

SECTION 11 NOTES:

---

**SECTION 12: DISCLAIMER**

---

**DISCLAIMER:** THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.